

Model Name Beam In & Out 200
 Materials Aluminium frame, PC diffuser
 Design by Peter Danczkay

Luminaire dimensions 200x3x5 cm
 Profile dimensions 50x30 mm
 Luminaire weight 2.3 kg

Light Direction In & Out



Net Lumens output 8075 lm
 Lumens LED output 13455 lm
 Voltage (constant voltage) 24 V
 Amperes / Watts 3.8 A / 90 W



LED Life 50 000 hrs L80/B30
 Warranty 1+2 years



Technical data is subject to change.

Document version v220415

| | | | | | |
|---------------------|-----|--------|-----------|--------|----|
| Light Direction | In | --> BI | Down | --> BD | BH |
| | Out | --> BO | In & Out | --> BH | |
| | Up | --> BU | Up & Down | --> BV | |

| | | | | | |
|----------|------------------|---------|--------|---------|-----|
| Size | Standard Sizes * | | | | |
| | 100 cm | --> 100 | 150 cm | --> 150 | 200 |
| | 200 cm | --> 200 | 250 cm | --> 250 | |

* Other sizes available upon request

| | | | | | | | | |
|------------|-------------------------|--------------------------|-------------------------|-----------------------------|-----------------------|----------------------------|------------------------------|---------------------------|
| Finish | Premium --> P | | | | | | | |
| | Deco Black 10 10M | Pearl White 20 20M | Golden Eye 30 30M | Silver Chalice 40 40M | Ruby Red 50 50M | Twilight Blue 60 60M | Champagne Brown 70 70M | Forest Green 80 80M |

* Use XX for high gloss finish and XXM for matt

** Additional custom colours can be selected by providing RAL or auto colour code

| | | | | | |
|----------|--------|-----------|-------|-----------|--------|
| Highline | --> H | | | | |
| | Gold | --> R1036 | White | --> R9016 | HR9011 |
| | Silver | --> R1036 | Black | --> R9011 | |

* Use M suffix for matt

** Any RAL colour, or special effects Powder coating available upon request

| | | | | | |
|----------------|--------------------------------|----------|---------------------------------------|----------|------|
| LED Colour | Warm White (Standard) - 3000°K | --> 9300 | Full Colour | --> RGB | 9400 |
| | Extra Warm White - 2700°K | --> 9270 | Colour & Warm White | --> R930 | |
| | Neutral White - 4000°K | --> 9400 | Colour & Neutral White | --> R940 | |
| | Tuneable white - 2700°K-4000°K | --> 2740 | * Contact us for other requirements * | | |

| | | | | | |
|--------------|------------------------------|---------|---------------------------------|--------|----|
| Mounting | * Canopy: | | Floor Standing: | | MM |
| | Single Point | --> CS | Marble Base | --> FM | |
| | Multiple Point | --> CM | Granite Base | --> FG | |
| | Vertical | --> CV | Thick Aluminium Base | --> FA | |
| | * Recessed No Canopy: | | Thin & Wide Steel Base | --> FS | |
| | Multiple Point | --> MM | Direct surface mounting: | | |
| | Vertical | --> MV | Flush Mount | --> D0 | |
| | * Cable Length | | ** Foot Mount | --> DF | |
| | 2.5m | --> 025 | ** Foot Length | | |
| | 4m | --> 040 | 6cm | --> 6 | |
| 6m | --> 060 | 12cm | --> 12 | | |

| | | | | | |
|-------------|----------------------------|--------|---------|--------|----|
| Control | Dimmable - W/o Dimmer | --> 00 | 1-10V | --> 40 | 20 |
| | Simple Remote | --> 10 | 0-10V | --> 50 | |
| | DALI / Push dim compatible | --> 20 | Casambi | --> 60 | |
| | DMX | --> 30 | | | |

Full model number example



BH200 - HR9011 9400 - MM025 - 20