



Model Name    Infinity Down 200  
 Materials     Aluminium frame, PC diffuser  
 Design by     Peter Danczkay

Luminaire dimensions    200x60x3 cm  
 Profile dimensions      30x27 mm  
 Luminaire weight        3.3 kg

Light Direction    Down



Net Lumens output      10245 lm  
 Lumens LED output    17080 lm



LED Life            50 000 hrs L80/B30  
 Warranty           1+2 years



Voltage (constant voltage)    24 V  
 Amperes / Watts                4.8 A / 114 W

Technical data is subject to change.

Document version v220415

Light Direction



In            --> II            Down        --> ID  
 Out         --> IO         In & Out    --> IH  
 Up          --> IU         Up & Down --> IV

ID

Size



Standard Sizes \*  
 150 cm        --> 150        200 cm        --> 200        200

\* Other sizes available upon request

Finish



Premium        --> P  
 Deco Black    10    20    Golden Eye    30    40    Silver Chalice    40    50    Ruby Red    50    60    Twilight Blue    60    70    Champagne Brown    70    80    Forest Green    80    80M

\* Use XX for high gloss finish and XXM for matt

\*\* Additional custom colours can be selected by providing RAL or auto colour code

Highline        --> H

Gold            --> R1036

White          --> R9016

HR9011

Silver          --> R1036

Black          --> R9011

\* Use M suffix for matt

\*\* Any RAL colour, or special effects Powder coating available upon request

LED Colour



Warm White (Standard) - 3000°K    --> 9300

Full Colour        --> RGB

9400

Extra Warm White - 2700°K    --> 9270

Colour & Warm White    --> R930

Neutral White - 4000°K        --> 9400

Colour & Neutral White    --> R940

Tuneable white - 2700°K-4000°K    --> 2740

\* Contact us for other requirements \*

Mounting



\* Canopy:

Single Point    --> CS

Multiple Point --> CM

Vertical         --> CV

Floor Standing:

Marble Base    --> FM

Granite Base    --> FG

Thick Aluminium Base --> FA

Thin & Wide Steel Base --> FS

MM

\* Recessed No Canopy:

Multiple Point --> MM

Vertical         --> MV

Direct surface mounting:

Flush Mount    --> D0

\*\* Foot Mount    --> DF

\* Cable Length

2.5m            --> 025

4m              --> 040

6m              --> 060

\*\* Foot Length

6cm            --> 6

12cm           --> 12

025

Control



Dimmable - W/o Dimmer    --> 00

1-10V        --> 40

Simple Remote                --> 10

0-10V        --> 50

DALI / Push dim compatible --> 20

Casambi     --> 60

DMX         --> 30

20

Full model number example



ID200 - HR9011 9400 - MM025 - 20