



Model Name Olala Down 120  
 Materials Aluminium frame, PC diffuser  
 Design by Peter Danczkay

Luminaire dimensions 120x120x3 cm  
 Profile dimensions 30x27 mm  
 Luminaire weight 2.5 kg

Light Direction Down



Net Lumens output 7805 lm  
 Lumens LED output 13005 lm


LED Life 50 000 hrs L80/B30

Warranty 1+2 years



Voltage (constant voltage) 24 V  
 Amperes / Watts 3.7 A / 87 W

Technical data is subject to change.



Document version v220415

Light Direction 	In	--> OI	Down	--> OD	OD
	Out	--> OO	In & Out	--> OH	
	Up	--> OU	Up & Down	--> OV	

Size 	Standard Sizes *				
	ø60 cm	--> 60	ø90 cm	--> 90	120
	ø120 cm	--> 120	ø150 cm	--> 150	

\* Other sizes available upon request

Finish 	Premium --> P							
	Deco Black	Pearl White	Golden Eye	Silver Chalice	Ruby Red	Twilight Blue	Champagne Brown	Forest Green
	10 10M	20 20M	30 30M	40 40M	50 50M	60 60M	70 70M	80 80M

\* Use XX for high gloss finish and XXM for matt

\*\* Additional custom colours can be selected by providing RAL or auto colour code

Highline	--> H			
	Gold --> R1036	White --> R9016		HR9011
	Silver --> R1036	Black --> R9011		

\* Use M suffix for matt

\*\* Any RAL colour, or special effects Powder coating available upon request

LED Colour 	Warm White (Standard) - 3000°K	--> 9300	Full Colour	--> RGB	9400
	Extra Warm White - 2700°K	--> 9270	Colour & Warm White	--> R930	
	Neutral White - 4000°K	--> 9400	Colour & Neutral White	--> R940	
	Tuneable white - 2700°K-4000°K	--> 2740	* Contact us for other requirements *		

Mounting 	<b>* Canopy:</b>			<b>Floor Standing:</b>		
	Single Point	--> CS		Marble Base	--> FM	
	Multiple Point	--> CM		Granite Base	--> FG	
	Vertical	--> CV		Thick Aluminium Base	--> FA	MM
				Thin & Wide Steel Base	--> FS	
	<b>* Recessed No Canopy:</b>			<b>Direct surface mounting:</b>		
	Multiple Point	--> MM		Flush Mount	--> D0	
	Vertical	--> MV		** Foot Mount	--> DF	
	<b>* Cable Length</b>			<b>** Foot Length</b>		
		2.5m	--> 025		6cm	--> 6
	4m	--> 040		12cm	--> 12	
	6m	--> 060			025	

Control 	Dimmable - W/o Dimmer	--> 00	1-10V	--> 40	
	Simple Remote	--> 10	0-10V	--> 50	20
	DALI / Push dim compatible	--> 20	Casambi	--> 60	
	DMX	--> 30			

Full model number example



OD120 - HR9011 9400 - MM025 - 20