




Model Name Olala In 120
 Materials Aluminium frame, PC diffuser
 Design by Peter Danczkay
 Light Direction In
 LED Life 50 000 hrs L80/B30
 Warranty 1+2 years



Luminaire dimensions 120x120x3 cm
 Profile dimensions 27x30 mm
 Luminaire weight 2.5 kg
 Net Lumens output 7805 lm
 Lumens LED output 13005 lm
 Voltage (constant voltage) 24 V
 Amperes / Watts 3.7 A / 87 W



Technical data is subject to change. Document version v220415

| | | | | | |
|---------------------|-----|--------|-----------|--------|----|
| Light Direction | In | --> OI | Down | --> OD | OI |
| | Out | --> OO | In & Out | --> OH | |
| | Up | --> OU | Up & Down | --> OV | |

| | | | | | |
|----------|------------------|---------|---------|---------|-----|
| Size | Standard Sizes * | | | | 120 |
| | ø60 cm | --> 60 | ø90 cm | --> 90 | |
| | ø120 cm | --> 120 | ø150 cm | --> 150 | |

* Other sizes available upon request

| | | |
|------------|-----------------|-----------|
| Finish | Premium | --> P |
| | Deco Black | 10 10M |
| | Pearl White | 20 20M |
| | Golden Eye | 30 30M |
| | Silver Chalice | 40 40M |
| | Ruby Red | 50 50M |
| | Twilight Blue | 60 60M |
| | Champagne Brown | 70 70M |
| | Forest Green | 80 80M |

* Use XX for high gloss finish and XXM for matt

** Additional custom colours can be selected by providing RAL or auto colour code

| | | |
|----------|-----------|-----------|
| Highline | --> H | HR9011 |
| Gold | --> R1036 | |
| Silver | --> R1036 | |
| White | --> R9016 | |
| | Black | --> R9011 |

* Use M suffix for matt

** Any RAL colour, or special effects Powder coating available upon request

| | | | | | |
|----------------|--------------------------------|----------|---------------------------------------|----------|------|
| LED Colour | Warm White (Standard) - 3000°K | --> 9300 | Full Colour | --> RGB | 9400 |
| | Extra Warm White - 2700°K | --> 9270 | Colour & Warm White | --> R930 | |
| | Neutral White - 4000°K | --> 9400 | Colour & Neutral White | --> R940 | |
| | Tuneable white - 2700°K-4000°K | --> 2740 | * Contact us for other requirements * | | |

| | | | | | |
|--------------|------------------------------|---------|---------------------------------|--------|----|
| Mounting | * Canopy: | | Floor Standing: | | MM |
| | Single Point | --> CS | Marble Base | --> FM | |
| | Multiple Point | --> CM | Granite Base | --> FG | |
| | Vertical | --> CV | Thick Aluminium Base | --> FA | |
| | * Recessed No Canopy: | | Thin & Wide Steel Base | --> FS | |
| | Multiple Point | --> MM | Direct surface mounting: | | |
| | Vertical | --> MV | Flush Mount | --> D0 | |
| | * Cable Length | | ** Foot Mount | --> DF | |
| | 2.5m | --> 025 | ** Foot Length | | |
| | 4m | --> 040 | 6cm | --> 6 | |
| 6m | --> 060 | 12cm | --> 12 | | |

| | | | | | |
|-------------|----------------------------|--------|---------|--------|----|
| Control | Dimmable - W/o Dimmer | --> 00 | 1-10V | --> 40 | 20 |
| | Simple Remote | --> 10 | 0-10V | --> 50 | |
| | DALI / Push dim compatible | --> 20 | Casambi | --> 60 | |
| | DMX | --> 30 | | | |

Full model number example



OI120 - HR9011 9400 - MM025 - 20