




Model Name Olala Up 60  
 Materials Aluminium frame, PC diffuser  
 Design by Peter Danczkay  
 Light Direction Up  
 LED Life 50 000 hrs L80/B30  
 Warranty 1+2 years



Luminaire dimensions 60x60x3 cm  
 Profile dimensions 30x27 mm  
 Luminaire weight 1.3 kg  
 Net Lumens output 3900 lm  
 Lumens LED output 6505 lm  
 Voltage (constant voltage) 24 V  
 Amperes / Watts 1.9 A / 44 W



Technical data is subject to change. Document version v220415

Light Direction 	In	--> OI	Down	--> OD	OU
	Out	--> OO	In & Out	--> OH	
	Up	--> OU	Up & Down	--> OV	

Size 	Standard Sizes *				60
	ø60 cm	--> 60	ø90 cm	--> 90	
	ø120 cm	--> 120	ø150 cm	--> 150	

\* Other sizes available upon request

Finish 	Premium	--> P						
	Deco Black	Pearl White	Golden Eye	Silver Chalice	Ruby Red	Twilight Blue	Champagne Brown	Forest Green
	10 10M	20 20M	30 30M	40 40M	50 50M	60 60M	70 70M	80 80M

\* Use XX for high gloss finish and XXM for matt

\*\* Additional custom colours can be selected by providing RAL or auto colour code

Highline	--> H			HR9011
Gold	--> R1036	White	--> R9016	
Silver	--> R1036	Black	--> R9011	

\* Use M suffix for matt

\*\* Any RAL colour, or special effects Powder coating available upon request

LED Colour 	Warm White (Standard) - 3000°K	--> 9300	Full Colour	--> RGB	9400
	Extra Warm White - 2700°K	--> 9270	Colour & Warm White	--> R930	
	Neutral White - 4000°K	--> 9400	Colour & Neutral White	--> R940	
	Tuneable white - 2700°K-4000°K	--> 2740	* Contact us for other requirements *		

Mounting 	<b>* Canopy:</b>		<b>Floor Standing:</b>		MM
	Single Point	--> CS	Marble Base	--> FM	
	Multiple Point	--> CM	Granite Base	--> FG	
	Vertical	--> CV	Thick Aluminium Base	--> FA	
	<b>* Recessed No Canopy:</b>		Thin & Wide Steel Base	--> FS	
	Multiple Point	--> MM	<b>Direct surface mounting:</b>		
	Vertical	--> MV	Flush Mount	--> D0	
	<b>* Cable Length</b>		** Foot Mount	--> DF	
	2.5m	--> 025	** Foot Length		
	4m	--> 040	6cm	--> 6	
6m	--> 060	12cm	--> 12		

Control 	Dimmable - W/o Dimmer	--> 00	1-10V	--> 40	20
	Simple Remote	--> 10	0-10V	--> 50	
	DALI / Push dim compatible	--> 20	Casambi	--> 60	
	DMX	--> 30			

Full model number example



OU60 - HR9011 9400 - MM025 - 20