



Model Name Olala Wall Up 90
 Materials Aluminium frame, PC diffuser
 Design by Peter Danczky

Luminaire dimensions 200x200x3 cm
 Profile dimensions 30x27 mm
 Luminaire weight 0.3 kg

Light Direction Up



Net Lumens output 650 lm
 Lumens LED output 1085 lm

LED Life 50 000 hrs L80/B30
 Warranty 1+2 years



Voltage (constant voltage) 24 V
 Amperes / Watts 0.4 A / 8 W



Technical data is subject to change.

Document version v220502

| | | | | | |
|---------------------|-----|---------|-----------|---------|-----|
| Light Direction | In | --> OWI | Down | --> OWD | OWU |
| | Out | --> OWO | In & Out | --> OWH | |
| | Up | --> OWU | Up & Down | --> OWV | |

| | | | | | |
|----------|------------------|---------|-------|---------|----|
| Size | Standard Sizes * | | | | |
| | 90 ° | --> 90 | 180 ° | --> 180 | 90 |
| | 270 ° | --> 270 | | | |

* Other sizes available upon request

| | | | | | | | | |
|------------|---------------|-------------|------------|----------------|-----------|---------------|-----------------|--------------|
| Finish | Premium --> P | | | | | | | |
| | Deco Black | Pearl White | Golden Eye | Silver Chalice | Ruby Red | Twilight Blue | Champagne Brown | Forest Green |
| | 10 10M | 20 20M | 30 30M | 40 40M | 50 50M | 60 60M | 70 70M | 80 80M |

* Use XX for high gloss finish and XXM for matt

** Additional custom colours can be selected by providing RAL or auto colour code

| | | | | |
|----------|------------------|-----------------|--|--------|
| Highline | --> H | | | |
| | Gold --> R1036 | White --> R9016 | | HR9011 |
| | Silver --> R1036 | Black --> R9011 | | |

* Use M suffix for matt

** Any RAL colour, or special effects Powder coating available upon request

| | | | |
|----------------|---|---------------------------------------|------|
| LED Colour | Warm White (Standard) - 3000°K --> 9300 | Full Colour --> RGB | 9400 |
| | Extra Warm White - 2700°K --> 9270 | Colour & Warm White --> R930 | |
| | Neutral White - 4000°K --> 9400 | Colour & Neutral White --> R940 | |
| | Tuneable white - 2700°K-4000°K --> 2740 | * Contact us for other requirements * | |

| | | | |
|-------------|-----------------------------------|----------------|----|
| Control | Dimmable - W/o Dimmer --> 00 | 1-10V --> 40 | |
| | Simple Remote --> 10 | 0-10V --> 50 | 20 |
| | DALI / Push dim compatible --> 20 | Casambi --> 60 | |
| | DMX --> 30 | | |

Full model number example



OWU90 - HR9011 9400 -

20