



Model Name Tri Up 90
Materials Aluminium frame, PC diffuser
Design by Peter Danczkay

Luminaire dimensions 101x90x3 cm
Profile dimensions 30x27 mm
Luminaire weight 3.6 kg

Light Direction Up



Net Lumens output 10805 lm
Lumens LED output 18010 lm

LED Life 50 000 hrs L80/B30
Warranty 1+2 years



Voltage (constant voltage) 24 V
Amperes / Watts 5.1 A / 121 W

Technical data is subject to change.

Document version v220417

| | | | | | |
|---------------------|-------------|-------------------|--|--|-----|
| Light Direction | In --> P3I | Down --> P3D | | | |
| | Out --> P3O | In & Out --> P3H | | | P3U |
| | Up --> P3U | Up & Down --> P3V | | | |

| | | | | | |
|----------|------------------|----------------|--|--|----|
| Size | Standard Sizes * | | | | |
| | 50 cm --> 50 | 70 cm --> 70 | | | 90 |
| | 90 cm --> 90 | 110 cm --> 110 | | | |

* Other sizes available upon request

| | | | | | | | | |
|------------|-------------------|--------------------|-------------------|-----------------------|-----------------|----------------------|------------------------|---------------------|
| Finish | Premium --> P | | | | | | | |
| | Deco Black 10 10M | Pearl White 20 20M | Golden Eye 30 30M | Silver Chalice 40 40M | Ruby Red 50 50M | Twilight Blue 60 60M | Champagne Brown 70 70M | Forest Green 80 80M |

* Use XX for high gloss finish and XXM for matt

** Additional custom colours can be selected by providing RAL or auto colour code

| | | | | |
|----------|------------------|-----------------|--|--------|
| Highline | --> H | | | |
| | Gold --> R1036 | White --> R9016 | | HR9011 |
| | Silver --> R1036 | Black --> R9011 | | |

* Use M suffix for matt

** Any RAL colour, or special effects Powder coating available upon request

| | | | |
|----------------|---|---------------------------------------|------|
| LED Colour | Warm White (Standard) - 3000°K --> 9300 | Full Colour --> RGB | 9400 |
| | Extra Warm White - 2700°K --> 9270 | Colour & Warm White --> R930 | |
| | Neutral White - 4000°K --> 9400 | Colour & Neutral White --> R940 | |
| | Tuneable white - 2700°K-4000°K --> 2740 | * Contact us for other requirements * | |

| | | | | | |
|--------------|------------------------------|-------------|---------------------------------|--|-----|
| Mounting | * Canopy: | | Floor Standing: | | |
| | Single Point --> CS | | Marble Base --> FM | | |
| | Multiple Point --> CM | | Granite Base --> FG | | |
| | Vertical --> CV | | Thick Aluminium Base --> FA | | MM |
| | | | Thin & Wide Steel Base --> FS | | |
| | * Recessed No Canopy: | | Direct surface mounting: | | |
| | Multiple Point --> MM | | Flush Mount --> D0 | | |
| | Vertical --> MV | | ** Foot Mount --> DF | | |
| | * Cable Length | | ** Foot Length | | |
| | 2.5m --> 025 | | 6cm --> 6 | | 025 |
| 4m --> 040 | | 12cm --> 12 | | | |
| 6m --> 060 | | | | | |

| | | | |
|-------------|-----------------------------------|----------------|----|
| Control | Dimmable - W/o Dimmer --> 00 | 1-10V --> 40 | |
| | Simple Remote --> 10 | 0-10V --> 50 | 20 |
| | DALI / Push dim compatible --> 20 | Casambi --> 60 | |
| | DMX --> 30 | | |

Full model number example



P3U90 - HR9011 9400 - MM025 - 20